

## Self Contained Mix Gas/ Pure Gas Filling

### Features:

PPS-5000 Mix Pumping Skid, Argon/ Nitrogen/CO2 service, complete with the following components:

- WCPH10/4 Cryogenic Pump for Argon/Nitrogen service to deliver a fixed flow rate of 5000 scfh at 3500 psi. Includes 3 hp motor, pressure relief valve, pressure gauge, pressure switch, drive pulleys and belt. All components enclosed and factory tested.
- V5KSS Ambient Air Vaporizer, 5000 scfh, 3500 psi maximum allowable working pressure.
- Mix Control Panel to control the manual filling of separate manifolds, 3000 psi rated. Includes:
  - Swing Arm - switch from CO2 to Inert
  - Gauges - High pressure and vacuum (with calibration certifications)
  - Valves - High pressure shut-off and vacuum.
  - Start/Stop Switches - High pressure and vacuum pumps.
- GAST Vacuum Pump
- Aluminum framed enclosure to mount above components.

NOTE: System can be upgraded to a flow rate of 10,000 scfh



### CONTROL YOUR INVENTORY

The Inert Gas Portable Pumping System is ideal for businesses that want to fill their own cylinders - and improve inventory control - without the high cost of installing a bulk tank.

Installation and Training • Technical Assistance • Parts and Service